

IDENTO
TAPE  ©



Exterior Grade Pipeline Identification





The Product.....

Identotape-eg is an exterior grade ID banding based on BS1710 and BS4800 standards. The product combines colour coding, arrows and service on one easy to use, self adhesive tape. It's unique design allows the tape to be turned through 360° whilst text and arrows are still orientated correctly.

The tape is made of durable polyester base material with a permanent acrylic adhesive backing. This combined with a UV filtered polyester overlam and easy peel release liner makes it very user friendly product. It has excellent adhesion properties to a variety materials including stainless steel and good resistance to water, oil and chemicals with a service temperature range of -40 to 150°C.

Identotape eg is available in 25meter rolls and in 50mm, 75mm, 100mm and 150mm wide formats in single or multiple languages. It's simple one piece, site application takes the hassle out of pipe identification whilst giving the job a durable, superior finish.

Order Code	Size
IDEG50*	50mm x 25mts
IDEG75*	75mm x 25mts
IDEG100*	100mm x 25mts
IDEG150*	150mm x 25mts

Minimum order quantity 3 rolls per service

When ordering please quote product code (Width), Basic Identification Colour (Edge band colour) Code Indication Colour (Central band colour) required text and flow arrows if applicable.

Typical delivery 2-3 weeks.

*Tapes can be printed in single or multiple languages including English, Russian and Azeri



© Patent and Design applied for.

It is CSI Manufacturing Limited policy to protect and defend it's intellectual property rights.



Product Specifications

Base Material	Industrial grade matt white polyester film.
Laminate	Optically clear, gloss polyester film with UV inhibitors
Adhesive	Industrial grade clear emulsion based permanent acrylic adhesive, highly crosslinked. Features high initial tack, ultimate adhesion and low adhesive ooze
Backing Paper	Siliconized glassine paper, woodfree, super calandered and extremely tough and tear resistant.
Dimensions	Rolls are available in 50mm, 75mm, 100mm and 150mm widths. All rolls are 25meters in length
Thickness	144 micron
Temperature Range	-40°C to +150°C
Chemical Resistance	Excellent chemical resistance including Acid, Alkalies and Salts.
Solvent Resistance	Excellent Solvent resistance including Oils, Heptanes, Kerosene and Alcohols.
Water Resistance	Excellent water resistance including Salt water
Standards	Colour - BS4800 and BS5252 Base Material - UL Recognised, file number MH27538 Layout - BS1710

